

# 2021 Jeep® Wrangler Rubicon 392 **SPECIFICATIONS**

Specifications are based on the latest product information available at the time of publication. All dimensions are in inches (millimeters) unless otherwise noted. All dimensions measured at curb weight with standard tires and wheels.

#### **GENERAL INFORMATION**

Vehicle Type	Sport-utility vehicle
Assembly Plant	Toledo Assembly Complex, Toledo, Ohio
EPA Vehicle Class	Multipurpose vehicle

### **BODY/CHASSIS**

Layout	Longitudinal, front engine, transfer case, four-wheel drive
Construction	Ladder-type frame, open steel and aluminum body

### **ENGINE: 6.4-LITER V-8**

Type and Description	90-degree V-type, liquid cooled
Displacement (cu. in. / cc)	392 cu. in. (6,417 cu. cm)
Bore x Stroke	4.09 x 3.72 (103.9 x 94.5)
Valve System	Pushrod-operated overhead valves, 16 valves with sodium-filled exhaust valves and hollow stem intake valves, 16 conventional hydraulic lifters, all with roller tips
Fuel Injection	Sequential, multi-port, electronic, returnless; Fuel Saver mode
Construction	Deep-skirt cast-iron block with cross-bolted main bearing caps, aluminum alloy heads with hemispherical combustion chambers
Compression Ratio	10.9:1
Power (SAE net) (hp / kW@rpm)	470 hp (354 kW) @ 6,000 rpm
Torque (SAE net) (lbft. / N•m)	470 lbft. (637 N•m) @ 4,300 rpm
Max. Engine Speed (rpm)	6,400 rpm (electronically limited)
Fuel Requirement	Premium 91 octane (R+M)/2 — required
Fuel Tank Capacity (gallons)	21.5

Oil Capacity	7 quarts (6.6 liters)
Coolant Capacity	14 quarts (13.25 liters)
Emission Controls	Dual close-coupled three-way catalytic converters, quad-heated oxygen sensors and internal engine features
Max. Gross Trailer Weight	3,500 lbs.
Assembly Plant	Saltillo Engine Plant, Saltillo, Mexico

# TRANSMISSION: 8HP75 AUTOMATIC, EIGHT-SPEED OVERDRIVE

Description	Adaptive electronic control or Electronic Range Select (ERS) driver-interactive manual control and electronically modulated torque converter clutch
Gear Ratios	
1st	4.71
2nd	3.13
3rd	2.10
4th	1.67
5th	1.28
6th	1.00
7th	0.84
8th	0.67
Reverse	3.30

# TRANSFER CASE: MP3022 SELEC-TRAC

Туре	Full-time
Operating Modes	4WD Auto; 4WD High; Neutral; 4WD Low
Low Range Ratio	2.72:1

## **AXLES**

Front	3rd Generation Dana 44
Differential type	Tru-Lock electronic locking
Rear	3rd Generation Dana 44
Differential type	Tru-Lok electronic locking
Axle ratios	3.73

#### **ELECTRICAL SYSTEM**

Architecture	Powernet
Alternator	180 amp
Battery	700 CCA, maintenance free

### **SUSPENSION**

Front	Solid axle, link coil, leading arms, track bar, coil springs, stabilizer bar
Stabilizer bar	Electronic sway-bar disconnect system
Shock type	High-pressure gas-charged FOX aluminum monotube shock absorbers with hydraulic rebound stop
Rear	Solid axle, link coil, trailing arms, track bar, coil springs, stabilizer bar
Shock type	High-pressure gas-charged FOX aluminum monotube shock

### **STEERING**

Туре	Electro-hydraulic power
Overall ratio	14.3:1
Turning diameter (curb-to-curb) (ft)	39.4
Steering Turns (lock-to-lock)	3.13
P/S pump	Electro-hydraulic

# **BRAKES**

Power-assisted, anti-lock brake system	
12.9 x 1.1 (330 x 28) vented rotor	
2 (51) twin-piston floating calipers	
13.6 x .86 (345 x 22) vented rotor	
2 (51) single-piston floating calipers	
	12.9 x 1.1 (330 x 28) vented rotor 2 (51) twin-piston floating calipers  13.6 x .86 (345 x 22) vented rotor

### **DIMENSIONS AND CAPACITIES**

Wheelbase	118.4 (3,008)
Overhang — Front	29.5 (749.8)
Overhang — Rear	40.3 (1,023)

Track — Front	64.4 (1,636)
Track — Rear	64.4 (1,636)
Overall Length (includes spare tire)	188.4 (4,786)
Overall Width	73.8 (1,875)
Overall Height	74.5 (1,893)
CLEARANCES	
Approach angle, degrees	44.5
Breakover angle, degrees	22.6
Departure angle, degrees	37.5
Ground clearance, inches	10.3
Water fording, inches	32.5
CURB WEIGHT (lbs.)	5,103
ACCOMMODATIONS	
Seating Capacity, F/R	2/3
SAE Total Interior Passenger Volume, (cu. ft. / cu. m)	103.3 (2.93)
FRONT	
Headroom	40.8 (1,036) hardtop / 42.8 (1,087) soft top
Legroom	40.8 (1,038)
Shoulder room	55.8 (1,417)
Hip room	53.9 (1,370)
Seat travel	8.1 (206)
EPA front volume index	54.6 (1.55)
REAR	
Headroom	40.3 (1,023) hardtop, 42.6 (1,082) soft top
Legroom	38.2 (970)
Knee clearance	61.6 (1,565.9)
Shoulder Room	55.8 (1,417)
Hip Room	55.9 (1,421)

EPA rear seat volume index (cu. ft. / cu. m)	48.7 (1.38)
Liftover height	30.8 (782)
Maximum cargo width at liftgate opening	47.9 (1,217)
Minimum cargo width at liftgate opening	41.5 (1,054)
Maximum cargo height at liftgate opening	36.0 (942.3)
Minimum cargo height at liftgate opening	35.7 (907.8)
Distance between wheelhouse interior trim	45.0 (1143)
SAE Cargo Volume	
Rear seat folded	67.4 cu. ft. (1.91)
Rear seat upright	27.7 cu. ft. (0.89)
Total passenger plus cargo volume, (cu. ft. / cu. m)	131 / 3.71
WHEELS	
Availability	Standard
Type and Material	Bead lock capable, high-gloss painted cast aluminum
Size	17 x 7.5 in.
TIRES	
Availability	Standard
Size and Type	LT285/70R17C, on/off-road, black sidewall
Mfr. And Model	BF Goodrich KO2 All-Terrain
Revs per Mile (km)	645 (401)
Availability	Optional
Size and Type	LT285/70R17C
2.=2 2a ) F 2	11203/10/11/0
Mfr. And Model	Falken Wildpeak M/T